

MATERIAL SAFETY DATA SHEET

SECTION 1- CHEMICAL PRODUCT AND COMPANY INDENTIFICATION

Product Name: Product Use / Class: Company Information: Solid Vinyl Tile/Plank [2.5mm (0.7mm)] Resilient Finished Floor Covering On behalf of Milliken Floorcovering 920 Milliken Road Spartanburg, SC 29304

Effective Date:

January 1, 2014

SECTION 2- PRODUCT COMPOSITION

None per OSHA Standard 29 CFR 1910.1200 & SARA Title III, Section 313. Products do not contain asbestos or formaldehyde.

SECTION 3- HAZARDS INDENTIFICATION

EMERGENCY OVERVIEW	
Physical state:	Solid
Appearance:	Rectangular or square pieces
Color:	Varies
Odor:	No appreciable odor
Intenerate Point:	> 176°F (80°C)
WARNING STATEMENTS	None
POTENTIAL HEALTH EFFECTS	
Likely Routes of Exposure	
Eye contact:	Possible irritation
Skin contact:	Possible, mild irritation
Inhalation:	Solid material. Be familiar with inhalation precautions for adhesives.
Ingestion:	Small amounts, if swallowed, are not expected to cause injury.
Chronic:	No known chronic effects
Other:	This product is a solid consumer good and is relatively non-toxic,
	presenting no known hazard to people except as noted under thermal
	decomposition by-products.
SECTION 4- FIRST AID MEASURES	
If in Eyes:	Flush with water, like any non-hazardous solid.
If on Skin:	If skin is irritated from handling product (transitory mechanical
	dermatitis), wash thoroughly with soap and water. Seek medical
	attention if condition persists.
If Inhaled:	None expected. Remove to fresh air and seek medical assistance if
	adverse reaction to adhesive occurs.
If Swallowed:	Seek medical assistance immediately.

SECTION 5- FIRE FIGHTING MEASURES



MATERIAL SAFETY DATA SHEET

	MATERIAL SALETT DATA SHEET	
Flash Point:	Not available	
Lower/Upper Explosive Limit (LEL/UEL) %:	Not available	
Auto- Ignition Temperature:	Not available	
OSHA Flammability Classification:	Not available	
Hazardous Products of Combustion:	Protect self from melted product & combustion products.	
Extinguishing Media:	Use foam, CO2, water spray, or dry chemical extinguishing agent, and	
	as appropriate for surrounding fire.	
Unusual Fire and Explosion Hazards:	None	
Fire Fighting Equipment:	Self-contained breathing apparatus and full protective clothing.	
SECTION 6- ACCIDENTAL RELEASE MEA	ASURES	
Personal precautions:	None. This is a non-hazardous material.	
Methods for clean-up:	Due to solid, inert properties scrap pieces may be simply swept up and	
	disposed of as a solid non-hazardous waste per local, state and federal	
	regulations.	
SECTION 7- HANDLING AND STORAGE		
Handling:	Install with adequate ventilation. Wash hands and arms thoroughly	
	after handling and before eating, drinking and storage.	
Storage:	Consult the Milliken Installation Guide for additional information on	
	handling and storage.	
SECTION 8- EXPOSURE CONTROLS / PERSONAL PROTECTION		
Engineering Controls:	Install in well ventilated areas	
Respiratory Protection:	Not normally required, unless adhesives or other installation	
	chemicals so warrant.	
Eye Protection:	Not normally required, unless adhesives or other installation	
	chemicals so warrant.	
Hand and Skin Protection:	Use of gloves is recommended since handling large quantities of	
	plank/tile may cause mechanical irritation around tips of fingers.	
Other Protective Equipment:	Not normally required, unless adhesives or other installation	
	chemicals so warrant.	
Hygienic Practices:	Wash hands before eating, smoking, or using toilet facilities. Do not	
	smoke in any chemical handling or storage area. Food or beverages	
	should not be consumed anywhere this product is handled or stored.	
	Wash thoroughly after handling.	
SECTION 9- PHYSICAL AND CHEMICAL PROPERTIES		

Appearance:	Solid, flooring planks or tiles
Physical State:	Solid, flooring planks or tiles
Odor:	No appreciable odor
Water Solubility:	Negligible
Specific Gravity:	1.4-2.0 (Water = 1.0)



MATERIAL SAFETY DATA SHEET

SECTION 10- STABILITY AND REACT	TIVITY
Conditions to avoid:	Stable
Materials to avoid:	Stable
Stability:	Stable. Volatilization or decomposition if heated over 392°F (200°C).
Hazardous reactions:	Will not occur.
Hazardous Polymerization:	Will not occur.
Hazardous Decomposition Products:	Thermal decomposition in the presence of air may yield carbon
	dioxide(CO ₂), carbon monoxide(CO) and possible hydrochloric
	acid(H ₂ S).

SECTION 11- TOXICOLOGICAL INFORMATION

None

SECTION 12- ECOLOGICAL INFORMATION

No ecological impact study information is available on this product.

SECTION 13- DISPOSAL CONSIDERATIONS

Material is inert and composed of virgin PVC material. Dispose of or recycle in accordance with local, state and federal guidelines.

SECTION 14- TRANSPORT INFORMATION

The information provided in this section is for information only. Please apply the appropriate regulations to properly classify your shipment for transport.

Material is non-hazardous and not regulated by USDOT.

SECTION 15- REGULATORY INFORMATION

Not Available

SECTION 16- OTHER INFORMATION

Per OSHA's Chemical Hazard Communication Standard (29CFR 1910.1200) Milliken provides Material Safety Data Sheets (MSDS's) for all of our sundry products (adhesives).

There are a variety of recommended work practices, installation techniques and safe handling guidelines in the Milliken installation guide. Because most floor installations require adhesives, it is recommended that the user review the Manufacturer's recommendations for adhesive spread rate, open time, proper ventilation, safe installation practices, etc. during installation.

DISCLAIMER

Although the information and recommendations set forth herein (hereinafter "information") are presented in good faith and believed to be correct as of the date hereof, the company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will the company be responsible for damages of any nature whatsoever resulting from the use or reliance upon information.