

OBEX™ MAT: CUT

SPECIFICATION SHEET DATE: 12 MARCH 2020

Textile Construction

Tufted, Cut Pile

Standard Size

85 x 60 cm	85 x 120 cm
85 x 150 cm	85 x 200 cm
85 x 300 cm	115 x 180 cm
115 x 200 cm	115 x 240 cm
115 x 300 cm	150 x 200 cm
150 x 250 cm	150 x 300 cm

Textile Yarn Type

100% Econyl® regenerated BCF polyamide, twisted & heat set multi/monofilament dual fibres

Textile Dye Method

DDI (Digital Dye Injection)

Backing Type

100% Nitrile Rubber

Backing Thickness

1.5 mm

Pile Height

7.3 mm

Lightfastness (ISO 105-B01)

> 6

Nominal Total Thickness

8 mm

Nominal Total Weight

3,180 g/m² (+/- 5%)

Flammability (EN ISO 13501)

Dfl-s1

Antistatic Behaviour (ISO 10965)

10⁷ff

Personal Charging (ISO 6356)

<2 kV (antistatic)

Slip Resistance (EN 13893)

Class DS

Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

ADA / BS 8300 / ISO 21542 Compliant

ISO Manufacturing Certification

ISO 9001

ISO Environmental Certification

ISO 14001

WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty



This product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.