

# OBEX™ MAT: MONO

SPECIFICATION SHEET DATE: 12 MARCH 2020

## Textile Construction

Tufted, Cut Pile

## Standard Size

85 x 60 cm	85 x 120 cm
85 x 150 cm	85 x 200 cm
85 x 300 cm	115 x 180 cm
115 x 200 cm	115 x 240 cm
115 x 300 cm	

## Textile Yarn Type

Econyl® 100% regenerated polyamide,  
twisted & heat-set monofilaments

## Textile Dye Method

Solution Dyed

## Backing Type

100% Nitrile Rubber

## Backing Thickness

1.5 mm

## Pile Height

11 mm

## Lightfastness (ISO 15-B02)

8 (maximum mark)

## Nominal Total Thickness

10 mm

## Nominal Total Weight

2,880 g/m<sup>2</sup> (+/- 5%)

## Flammability (EN ISO 13501)

Dfl-s1

## Antistatic Behaviour (ISO 10965)

10<sup>11</sup>ff

## Personal Charging (ISO 6356)

<2 kV (antistatic)

## Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

## ADA / BS 8300 / ISO 21542 Compliant

## ISO Manufacturing Certification

ISO 9001

## ISO Environmental Certification

ISO 14001

## WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty



This product is covered by one or more patents,  
published applications and/or patents pending.  
Specifications are subject to normal manufacturing  
tolerances and may be changed without prior notice.  
Copies of actual test results are available upon request.