

OBEX™ TILE: LOOP

SPECIFICATION SHEET DATE: 30 MARCH 2020

MODULAR TILE

Construction

Tufted, Multi-Level Loop

Tile Size

50 cm x 50 cm

Textile Yarn Type

ECONYL® Type 6 and Monofilament

Dye Method

Solution-Dyed

Nominal Tufted Face Weight

946 g/m²

Gauge

1/12

Stitches Per Centimeter

28.70

Tufts

2,100/100 cm²

Nominal Pile Height

6.48 mm

Nominal Total Thickness

9.9 mm

Nominal Total Weight

3,540 g/m²

Backing Type

PVC-Free WellBAC™ Comfort Cushion (Available with TractionBack®)

Recycled Content by Total Weight

33.3% Pre-Consumer
6.6% Post-Consumer

Flammability (Radiant Panel ASTM-E-648)

≥0.45 (Class I)

Smoke Density (NPA-258-T or ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70) or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 21°C

≤3.5 KV, Permanent Conductive Fibre

Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

Indoor Air Quality —

CRI Green Label Plus™
GLP.793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

12 Tiles per box (3m²)

WARRANTIES

1-Year Manufacturing Defect Warranty
5-Year Wear Warranty

Lifetime Face Fibre Wear
Lifetime Antistatic
Lifetime Floor Compatibility
Lifetime Colour Pattern Permanency
Lifetime Floor Release

Lifetime Cushion Resiliency
Lifetime Moisture Resistance
Lifetime Delamination of Backing
Lifetime Staining/Soiling (StainSmart®)
Lifetime Dimensional Stability

Lifetime Tuft Bind
Lifetime Edge Ravel
Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.