

OBEX™ BAR: MONO

11 mm, 16 mm

SPECIFICATION SHEET DATE: 27 AUGUST 2019

BAR PROFILE

Bar Material

Extruded aluminium profile with foam base layer

Profile Section

69 mm

Nominal Profile Thickness

9 mm

14 mm

Nominal Total Thickness

11 mm

16 mm

Bar Colour

Aluminium (Silver)

Static Loading

Min 50KN (5000 kg-Force)

TEXTILE

Textile Construction

Cut Pile

Textile Yarn Type

Econyl® 100% regenerated polyamide, twisted & heat-set monofilaments

Textile Dye Method

Solution Dyed

Lightfastness (ISO 105-B01)

8 (maximum mark)

ISO Manufacturing Certification

ISO 9001

ISO Environmental Certification

ISO 14001

WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty

Nominal Total Weight

11 mm: 8,295 g/m²

16 mm: 11,595 g/m²

Installation Width and Length

Maximum Width: 2.7 m

Maximum Length: Unlimited

Fire Classification (EN ISO 13501)

Dfl-s1

Product Classification (BS EN 1307)

Class 32/LC3

Slip Resistance (EN 13893)

Class DS

Antistatic Behaviour (ISO 10965)

Antistatic

Dimensional Stability (-25°C to +70°C)

< 0.75%

Rolling Load Weight - Freelaid

Min 50KN (5000 kg-Force)

Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

ADA / BS 8300 / ISO 21542 Compliant



This product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.