

OBEX™ GRID: VINYL

11 mm Closed

SPECIFICATION SHEET DATE: 27 AUGUST 2019

MODULAR GRID

Grid Material

100% UV-Resistant PVC

Grid Size

Nominal: 210 mm x 210 mm

Installed Usable: 198 mm x 198 mm

Nominal Grid Thickness

11 mm

Nominal Total Thickness

11 mm

Grid Colour

Black

Nominal Total Weight

7,150 g/m²

Fire Classification (EN ISO 13501-2010)

Bfl-s1

Dynamic co. of Friction (EN 13893:2003)

DS

Dimensional Stability (-25°C to 60°C)

+/- 1%

Static / Dynamic Loading

36 kg/cm²

Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water
Extraction or Pressure Wash

Rolling Load Weight - Freelaidd

500 kg

Grids Per Box

30 (1.176 m²)

ADA / BS 8300 / ISO 21542 Compliant

ISO Manufacturing Certification

ISO 9001


ISO Environmental Certification

ISO 14001

WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty



This product is covered by one or more patents,
published applications and/or patents pending.
Specifications are subject to normal manufacturing
tolerances and may be changed without prior notice.
Copies of actual test results are available upon request.