

OBEX™ HALF BAR: MONO

11 mm, 16 mm, 22 mm

SPECIFICATION SHEET DATE: 27 AUGUST 2019

HALF BAR PROFILE

Bar Material

Extruded aluminium profile with foam base layer

Profile Section

33 mm

Nominal Profile Thickness

9 mm
14 mm
20 mm

Nominal Total Thickness

11 mm
16 mm
22 mm

Bar Colour

Aluminium (Silver)

Static Loading

Min 50KN (5000 kg-Force)

TEXTILE

Textile Construction

Cut Pile

Textile Yarn Type

Econyl® 100% regenerated polyamide, twisted & heat-set monofilaments

Textile Dye Method

Solution Dyed

Lightfastness (ISO 105-B01)

8 (maximum mark)

ISO Manufacturing Certification

ISO 9001

ISO Environmental Certification

ISO 14001

WARRANTIES

1-Year Manufacturing Defect Warranty
5-Year Wear Warranty

Nominal Total Weight

11 mm: 9,850 g/m²
16 mm: 12,850 g/m²
22 mm: 15,050 g/m²

Installation Width and Length

Maximum Width: 2.7 m
Maximum Length: Unlimited

Fire Classification (EN ISO 13501)

Dfl-s1

Product Classification (BS EN 1307)

Class 32/LC4

Slip Resistance (EN 13893)

Class DS

Antistatic Behaviour (ISO 10965)

Antistatic

Dimensional Stability (-25°C to +70°C)

< 0.75%

Rolling Load Weight - Freelaid

Min 50KN (5000 kg-Force)

Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

ADA / BS 8300 / ISO 21542 Compliant



This product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.