

OBEX™ ROLL: CUT

SPECIFICATION SHEET DATE: 27 AUGUST 2019

Textile Construction

Tufted, Cut Pile

Roll Size

2 m x 18 m

Textile Yarn Type

100% Econyl® regenerated BCF polyamide,
twisted & heat set multi/monofilament dual fibres

Textile Dye Method

DDI (Digital Dye Injection)

Backing Type

100% PVC

Pile Height

7.3 mm

Pile Density

0.129 g/cm³

Lightfastness (ISO-B01)

<6

Nominal Total Thickness

10 mm

Nominal Total Weight

3,530 g/m² (+/- 5%)

Flammability (EN ISO 13501)

Cfl-s1

Antistatic Behavior (ISO 10965)

10¹²ff

Personal Charging (ISO 6356)

< 2 kV (antistatic)

Wear Resistance

Class 32

Slip Resistance (EN 13893)

Class DS

Recommended Maintenance

Daily Vacuuming and Quarterly Hot Water Extraction

ADA / BS 8300 / ISO 2152 Compliant

ISO Manufacturing Certification

ISO 9001

ISO Environmental Certification

ISO 14001

WARRANTIES

1-Year Manufacturing Defect Warranty

5-Year Wear Warranty



This product is covered by one or more patents,
published applications and/or patents pending.
Specifications are subject to normal manufacturing
tolerances and may be changed without prior notice.
Copies of actual test results are available upon request.