

GRAND PLAZA 36

Base

Modular Tile

Construction

Tufted, Patterned Cut Pile

Tile Size

1 m x 1 m (39.4" x 39.4")

Yarn Type

Milliken-Certified WearOn® Nylon Type 6,6

Stain Resist / Soil Release

StainSmart®

Dye Method

DDI (Digital Dye Infusion)

Tufted Face Weight

36 oz/yd² (1,220.6 g/m²)

Gauge

1/10

Stitches Per Inch

11.4

Tufts

114/in² (1,766/100 cm²)

Finished Pile Height

0.25" (6.35 mm)

Average Density (Finished)

5,184

Standard Backing

PVC-Free WellBAC™ Comfort Plus Cushion

Available with TractionBack®

Recycled Content by Total Weight

Standard Backing: 23% Pre-Consumer, Post-Consumer
NSF 140 Platinum Backing Option: Pre-Consumer, Post-Consumer

Nominal Total Thickness

0.42" (10.7 mm)

Nominal Total Weight

120.0 oz/yd² (4,069 g/m²)

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

Static Electricity (AATCC-134) 20%

R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating

(TARR)

Severe Traffic End-Use Applications

Recommended Maintenance

MilliCare® Textile and Carpet Care Service Network

Indoor Air Quality—CRI Green Label Plus™

GLP0793, Carpet Category 5Y

Recommended Installation Method(s)

Monolithic

WARRANTIES

Wear - 10 Year/ 10% Fiber Loss

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel

Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.