

SKINNY STRIPE

Base

Modular Tile

Construction

Tufted, Textured Loop

Tile Size

1 m x 1 m (39.4" x 39.4")
 50 cm x 50 cm (19.7" x 19.7")
 25 cm x 1 m (9.84" x 39.4")

Yarn Type

Milliken-Certified WearOn® Nylon
 Type 6,6

Stain Resist / Soil Release

StainSmart®

Dye Method

DDI (Digital Dye Infusion)

Tufted Face Weight

15 oz/yd² (508.6 g/m²)

Gauge

1/12

Stitches Per Inch

9.8

Tufts

117.6/in² (1,821/100 cm²)

Finished Pile Height

0.13" (3.30 mm)

Average Density (Finished) 6,541

Standard Backing

PVC-Free WellBAC™ Comfort Cushion
 Available with TractionBack®

Recycled Content by Total Weight

Standard Backing: 39.3% Pre-Consumer, 0.0% Post-Consumer
 NSF 140 Platinum Backing Option: 28.6% Pre-Consumer, 10.7% Post-Consumer

Nominal Total Thickness

0.28" (7.1 mm)

Nominal Total Weight

89.2 oz/yd² (3,024 g/m²)

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

Static Electricity (AATCC-134) 20%

R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Texture Appearance Retention Rating

(TARR)

Severe Traffic End-Use Applications

Recommended Maintenance

MilliCare® Textile and Carpet Care
 Service Network

Indoor Air Quality—CRI Green Label Plus™

GLP0793, Carpet Category 5Y

Recommended Installation Method(s)

Pattern Specific

WARRANTIES

Wear - 10 Year/ 10% Fiber Loss
 Lifetime Antistatic
 Lifetime Floor Compatibility
 Lifetime Floor Release

Lifetime Cushion Resiliency
 Lifetime Moisture Resistance
 Lifetime Delamination of Backing
 Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability
 Lifetime Tuft Bind
 Lifetime Edge Ravel
 Flammability



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.